

Asphalt Paint

A solvent free paint for internal and external asphalt and bitumen surfaces



Watco Asphalt Paint is the ideal way to seal, protect and colour asphalt and similar surfaces. The thick, flexible coating is easy to apply by brush or roller and is available in a range of attractive colours.

Many Uses

Watco Asphalt Paint is ideal for use in warehouses, plant rooms, asphalt walkways on roofs, car park bays and for line marking on tennis courts, playgrounds etc.

- Only one coat normally required
- Flexible, waterproof membrane
- Excellent resistance to UV and weathering
- Can be applied to damp surfaces
- Also adheres well to concrete, brick, masonry and similar porous surfaces
- Suitable for light to medium traffic.
- Easy to recoat in heavier wear areas.

Tile Red



White



Light Blue



Light Grey



Green



Black



Appearance

Coloured, low to mid sheen finish depending upon substrate and number of coats applied.

Availability

Available in 6 colours in 5 litre units.

Coverage

5 litres covers 20-30m² per coat depending on the texture of the substrate. One coat normally required.

The coverage rate does not allow for filling the crevices and texture of a tarmac or asphalt surface. Using the product in this way will greatly reduce coverage and extend drying time.

Shelf Life

At least one year in manufacturer's unopened containers.

Storage

Store in cool, dry conditions away from direct sunlight.

Surface Preparation

Watco Asphalt Paint can be applied to asphalt, tarmac, porous concrete, masonry, bricks, breeze blocks and most metals. Ensure the surface is clean, sound and dry (slightly damp is acceptable). Watco Bio-D is a solvent free degreaser which can be used on asphalt and similar surfaces. Watco Asphalt Paint can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are dulled using abrasive paper.

Application

Apply Watco Asphalt Paint by brush or medium pile type roller. One coat is generally sufficient although a second coat may be required on very porous or very rough surfaces. Avoid applying too thickly. Do not apply externally if rain or frost is forecast or if the temperature is below 10°C. The second coat should be applied after approximately 1 hour.

In exceptional temperature conditions advice should be obtained from Watco's Technical Department.

Curing Time

The product will cure sufficiently in approximately 24 hours to accept light traffic, but allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay curing.

Cleaning of Applicators

Clean applicators in warm soapy water before the product has started to cure.

Limitations

Watco Asphalt Paint is intended as a decorative finish only and will not bind or fill weak or defective asphalt surfaces. Do not apply in areas which will be constantly under water.

Safety

All product labels provide general safety information.

Material Safety Data Sheets are available.

Food products must be removed from the area during application and cure.

Watco Bio-D

For preparatory degreasing. A powerful solvent free degreaser that removes oil and grease. Coverage 20m² per 5 litres.

Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

**Watco UK Limited**

Watco House, Filmer Grove, Godalming, Surrey GU7 3AL, England

Tel: 01483 42 5000 • Fax: 01483 42 8888

www.watco.co.uk • E-mail: sales@watco.co.uk

© Watco UK Ltd June 2005



ISO 9001 quality
standard for supply