

# Anti-Slip Traffic Paint

**A tough, slip-resistant coating for interior or exterior use**



Watco Anti-Slip Traffic Paint contains a pre-dispersed lightweight aggregate which provides a finely textured anti-slip surface. It produces a more evenly textured finish than conventional anti-slip coatings where grit is sprinkled into wet paint. The product is easily applied by roller.

One coat is generally sufficient on most surfaces although Yellow and White may require a second coat on contrasting backgrounds

## Many Uses

Highlight external walkways, car park spaces and markings etc. Apply colour codes to safe

or hazardous pedestrian and vehicle areas. Smarten up drab, grey asphalt and concrete. Also ideal for tennis courts, playgrounds etc.

- Suitable for asphalt or concrete
- Excellent resistance to UV
- Fine texture offers slip resistance for pedestrians
- Only one coat is generally required
- Can be applied to damp surfaces
- No primer required
- Safety Blue is suitable for disabled car park bays



While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered

## Watco Anti-Slip Traffic Paint

### Appearance

Matt, finely textured surface.

### Availability

Available in 7 colours in 5 litre units.

### Coverage

5 litres covers 15-20m<sup>2</sup> per coat depending on the texture of the substrate. One coat normally required. Do not use the paint to fill the texture of open tarmac or asphalt surfaces. This will reduce the coverage rate and extend the drying time of the paint. It could also reduce the ability of asphalt to drain which may lead to slip problems in wet areas.

### Shelf Life

At least one year in manufacturer's unopened containers.

### Storage

Store in cool, dry conditions away from direct sunlight.

### Surface Preparation

Watco Anti-Slip Traffic Paint can be applied to asphalt, tarmac and porous concrete. Ensure the surface is clean, sound and dry (slightly damp is acceptable). Watco Bio-D is a bio-degradable solvent free degreaser which can be used on asphalt and similar surfaces. Watco Anti-Slip Traffic Paint can be applied to existing paint provided all poorly bonded material is removed and glossy surfaces are dulled using abrasive paper.

### Application

Stir contents thoroughly to blend in any settlement. Apply Watco Anti-Slip Traffic Paint by brush or medium pile type roller. One coat is generally sufficient although a second coat may be required on very porous or rough surfaces.

Avoid applying too thickly. The fine texture may not be immediately apparent as the product is first applied. The texture develops further as the paint dries. Do not apply externally if rain or frost are forecast or if the temperature is below 10°C. The second coat should be applied after approximately 1 hour. In exceptional temperature conditions advice should be obtained from Watco's Technical Department.

### Curing Time

The product will cure sufficiently in approximately 24 hours to accept light traffic, but allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay curing.

### Cleaning of Applicators

Clean applicators in warm soapy water before the product has started to cure.

### Limitations

In common with other coatings of this type, if this product is used externally it could contribute to a possible slip hazard on poorly drained surfaces in heavy rain/flood conditions. Do not apply in areas which will be constantly under water.

### Safety

All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.

### Watco Bio-D

For preparatory degreasing. A powerful solvent-free degreaser that removes oil and grease. Coverage 20m<sup>2</sup> per 5 litres.

### Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.



### Watco UK Limited

Watco House, Filmer Grove, Godalming, Surrey GU7 3AL, UK  
Tel: 01483 42 5000 • Fax: 01483 42 8888  
www.watco.co.uk • E-mail: sales@watco.co.uk

© Watco UK Ltd December 2005



ISO 9001 quality standard for supply