



# GRESTEC TILES

## CERAMIC, STONE & GLASS TECHNOLOGY

Grestec Tiles Ltd. Unit 7, Wheelbarrow Park Estate  
Pattenden Lane, Marden, Kent. TN12 9QJ

Tel: 0845 130 2241 Fax: 0845 130 2242

E-mail: mail@grestec.co.uk Website: www.grestec.co.uk

## ROAN COLLECTION - NATURAL PORCELAIN STONEWARE

### Maintenance Technical Sheet

#### INITIAL WASHING

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

<b>Product:</b>	<b>Deterdek</b> (acid floor cleaner) – 1:5 diluted in water.
<b>Coverage:</b>	<b>Deterdek:</b> 5 l per 100m <sup>2</sup> (when used 1:5 diluted in water).
<b>Equipment:</b>	Single-disc professional polisher fitted with a green pad, liquid vacuum cleaner, long-handled brush, and cloth.
<b>Procedure:</b>	After the floor is swept and soaked with water, spread the diluted <b>Deterdek</b> (1:5 in water) on it; then scour with the single-disc professional polisher fitted with a brown pad or with a long-handled brush. Vacuum the residue, rinse the floor very well and then still mop up with a liquid vacuum cleaner or a cloth.

#### ROUTINE MAINTENANCE

The aim of the routine maintenance is to remove dirt and scuff marks. The routine maintenance must be carried out regularly.

<b>Product:</b>	<b>Filacleaner</b> – diluted in water as required by the degree of dirt.
<b>Equipment:</b>	Cloth.
<b>Procedure:</b>	Dilute <b>Filacleaner</b> in warm water (e.g. half a beaker of detergent in five litres of water). Wipe a cloth, wet with this solution, over the floor. Rinse the floor only in case of concentrated solutions of <b>Filacleaner</b> (e.g. 1:10 in water).

#### SPECIAL MAINTENANCE

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.

<b>Product:</b>	<b>Fila PS/87</b> – 1:5 diluted in water.
<b>Coverage:</b>	5 l per 100m <sup>2</sup> (when used diluted 1:5)
<b>Equipment:</b>	Single-disc professional polisher (green pad, long-handled brush, liquid vacuum cleaner, cloth).
<b>Procedure:</b>	Dilute <b>Fila PS/87</b> at 1:5 in water. Apply it to the floor previously soaked with water and leave to act for a few minutes. Then scrub with a single-disc professional polisher (fitted with a green pad) or with a long-handled brush, mopping up the residue with a liquid vacuum cleaner or cloth.

*Instructions for use and application of the product we suggest are the outcome of precise verifications that have been carried out in Fila's laboratories. Nevertheless there are some elements we cannot control: condition of the surface before the treatment, characteristics/surface finishing of the material which are particularly rare or not specified, environment conditions. Therefore we always recommend trying the products first on a little portion of the floor. Fila SpA guarantees the quality of its product but neither they nor Grestec Tiles Ltd take on responsibility for an incorrect use of them.*