

L20/480 SLIDING HYGIENIC GRP DOORSETS

Wen-plast K Type Bi-Parting Sliding Door Sets

- Manufacturer : DorteK Ltd St Mark Street Hull HU8 7ED United Kingdom
Tel +44 (0)1482 226848 Fax +44 (0) 1482 226843 e-mail info@dortek.com
- Door : The doors shall be seamless glass-fibre reinforced polyester moulded around non-organic hi-density closed cell core. Door leaf wider than 1125mm will have a hygienic gel coat vertical joint.
- Reference : Wen-Plast Type K Bi-parting – B-SL or HB-SL sliding door
- Sizes : *See list of manufacturers standard sizes*
- Core : High density closed cell C.F.C and H.F.C free
thermal conductivity 0.05 W/m sq
- Facing : Seamless hygienic moulded polyester, 2.5mm thick.
moisture absorption zero.
- Door leaf : 40mm thick.
- Finish : Smooth non-porous gelcoat finish with built in colour
- Colour : Standard white or choice of 20 colours see chart or RAL / BS to order.
- Door frame : Anodised aluminium angle or steel profile to suit wall thickness finish stainless steel or powder coated or anodised aluminium to suit wall thickness
specify wall thickness
- Ironmongery : 2 No Stainless steel flush / pull handles. *Specify. Locks etc*
- Track : Aluminium rail system with nylon bearings
- Guide : Internal bottom track with nylon guide
- Glazing : Triple glazed with laminate safety glass or acrylic outer panes finished flush with both faces of door Size 200 x 300mm or 200 x 600mm or 300 x 600mm or 400 x 600mm position 165mm from leading edge or other sizes on request
- Canopy : White coated or Stainless steel with sloping top.
- Operation : Manual (Not self closing) or Electrical automation micro processor controlled with safety photo-cell, in-built safety sensor to open the door if obstructed operated with 2 push buttons or 2 touchless sensors or 2 infra red detectors.
Specify Battery back up to operate door in case of power failure